



Ghandhara DF (Pvt) Ltd.

Head Office:
Head Office: F-3, Hub Chowki Road,
S.I.T.E, Karachi. UAN # 021-111-190-190,
Tel: 021-32556901-10,
Fax: 021-32556911-12

Rawalpindi Office:
Gammon House Plot
no. 400/2 Peshawar Road, Rawalpindi.
Ph: 051-5465742
Fax: 051-5465503

Lahore Office:
Chowk Al-Saeed, Nain Sukh,
Saglyan By Pass, Lahore.
Ph: 042-37163931
Fax: 042-37163932

 DongFeng Pakistan

 www.ghandharadf.com



■ DONGFENG DFL4181A (DF-230) 4x2 Prime Mover

Vehicle Weight

G.C.M	40,000 kg
Curb Weight (chassis)	7300 kg

Chassis Dimensions (mm)


Overall Chassis Length	6080
Cab Width	2500
Cab Height (Unladen)	3030
Wheel Base	3500
Front Overhang	1480
Rear Overhang	1100
Maximum Gradeability	30%
Maximum Velocity (Km/h)	80

Frame Profile Dimensions (mm)

Frame Width (front)	940
Frame Width (rear)	860
Section Height	300
Section Width	90


Clutch

Type	
Plate Diameter	φ430mm
Operating System	Hydraulic control with air booster, pushing



Engine

Type	CUMMINS C-230
Emission Level	Euro II
Maximum Power	(230HP at 2200rpm)
Maximum Torque	861 Nm at 1300rpm
Number of Cylinders	6
Displacement (lit)	8,300
Cylinder bore (mm)	114
Stroke (mm)	135
System	Water cooled, turbocharged, after cooled, direct injection, exhaust brake system, heating for starting.



Gear Box

Type	RT-11509C DD
Number of Gears	9 Forward gears & 1 reverse

Low Speed	1 st	2 nd	3 rd	4 th	5 th	6 th	7 th	8 th	R
12.42	8.62	6.08	4.53	3.38	2.47	1.81	1.35	1.00	12.99



Axle

Front:	Elliott type, I beam section
Load Capacity	7 ton
Rear:	Single reduction axle, ratio 5.143
Load capacity(ton)	13 ton



Suspension

Front:	Leaf spring
Rear:	Leaf spring

Fuel Tank

Type	Steel fuel tank with lockable cap
Capacity	400 Liters

Brake System

Full air brake system, split pneumatic circuit, parking spring brake acting on rear axles, exhaust brake (ABS).

Cab

Sleeper cab, forward control type, low roof, new face, all welded steel cab. Electrical cab tilting, front and rear mechanical cab suspension, adjustable driver's seat, air conditioning system, electrical windows, central lock.

Tyres Battery

11.00-20/11.00R20	Voltage (V)	24
	Battery capacity (A.h)	165x2

Note : The above mentioned parameters are only for your reference, please check real vehicle referring to actual equipment.

Dealer


DONGFENG
Trucks